



Regal® Select Exterior Paint- High Build

Regal Select Exterior High Build is a thick, high-build formula tinted on our proprietary Gennex® colorant system. It is engineered for optimum hide and adheres powerfully to exterior substrates. It is also mildew and stain resistant.

Key Advantages:

An advanced high-build formula engineered for optimum hide and fewer coats.

Code	Product	Colors	Bases	Vol Sol.	Recoat	Cov. sq.ft.	DFT mils	VOC gm./l.	Specifications†
N400	Regal® Select Exterior High-Build Flat Finish	White	1-4	44.4%	4 hrs.	250-350	2.3	42	MPI 10
N401	Regal® Select Exterior High-Build Low Lustre Finish	White	1-4	43.0%	4 hrs.	250-350	2.3	40	MPI 15, 315
N403	Regal® Select Exterior High-Build Soft Gloss Finish	White	1-4	40.5%	4 hrs.	275-375	2.0	43	MPI 11, 311

Product Description	Features/Benefits	Notes
N400: A premium quality, high-build, 100% acrylic coating that is easy to apply and has superior coverage and durability. It is resistant to fading, cracking, and peeling.	<ul style="list-style-type: none"> • High Build Formula - Allows for a thicker coat for better hide and coverage • Excellent flow & leveling - Outstanding surface smoothness and easy application • Can be applied down to 40° F - Extends the painting season • Durable Finish - Resists fading, cracking, and peeling • Quick Drying - Saves time 	Do not apply when temperatures are below 40° F (4.4° C).
N401: A premium quality, high-build, 100% acrylic coating that is easy to apply and has superior coverage and durability. It is resistant to fading, cracking, and peeling.	<ul style="list-style-type: none"> • High Build Formula - Allows for a thicker coat for better hide and coverage • Excellent flow & leveling - Outstanding surface smoothness and easy application • Can be applied down to 40° F - Extends the painting season • Durable Finish - Resists fading, cracking, and peeling • Quick Drying - Saves time 	Do not apply when temperatures are below 40° F (4.4° C).
N403: A premium quality, high-build, 100% acrylic coating that is easy to apply and has superior coverage and durability. It is resistant to fading, cracking, and peeling.	<ul style="list-style-type: none"> • High Build Formula - Allows for a thicker coat for better hide and coverage • Excellent flow & leveling - Outstanding surface smoothness and easy application • Can be applied down to 40° F - Extends the painting season • Durable Finish - Resists fading, cracking, and peeling • Quick Drying - Saves time 	Do not apply when temperatures are below 40° F (4.4° C).