



## Ultra Spec® EXT

A low VOC, professional-quality exterior coating designed to meet the needs of professional painting contractors, facility managers, property managers, and specifiers.

### Key Advantages:

Formulated to provide excellent durability for maximum protection. It features superior coverage, ease of application and enhanced adhesion to a wide variety of surfaces. Ultra Spec EXT can be applied in temperatures as low as 40° F.

Code	Product	Colors	Bases	Vol Sol.	Recoat	Cov. sq.ft.	DFT mils	VOC gm./l.	Specifications <sup>†</sup>
N447	Ultra Spec® EXT Flat Finish	White	1-4	37.4%	4 hrs.	350-450	1.5	45	MPI 10
N448	Ultra Spec® EXT Satin Finish	White	1-4	37.7%	4 hrs.	350-450	1.5	46	MPI 15
N449	Ultra Spec® EXT Gloss Finish	White	1-4	37.8%	4 hrs.	350-450	1.5	46	MPI 11

Product Description	Features/Benefits	Notes
<b>N447:</b> A professional quality 100% acrylic exterior flat finish recommended for wood, hardboard, vinyl, aluminum, and fiber cement sidings; unglazed brick, concrete, stucco, cinder block, and primed metal.	<ul style="list-style-type: none"> <li>• 100% acrylic latex formula - Delivers superior hide and coverage</li> <li>• Low VOC - Meets the strictest environmental standards in the industry</li> <li>• Can be applied down to 40° F - Extends the painting season</li> </ul>	Do not apply when air and surface temperatures are below 40° F (4.4° C). Do not paint vinyl siding or trim darker than the original color in general.
<b>N448:</b> A professional quality 100% acrylic exterior satin finish recommended for wood, hardboard, vinyl, aluminum, and fiber cement sidings; unglazed brick, concrete, stucco, cinder block, and primed metal.	<ul style="list-style-type: none"> <li>• 100% acrylic latex formula - Delivers superior hide and coverage</li> <li>• Low VOC - Meets the strictest environmental standards in the industry</li> <li>• Can be applied down to 40° F - Extends the painting season</li> </ul>	Do not apply when air and surface temperatures are below 40° F (4.4° C). Do not paint vinyl siding or trim darker than the original color in general.
<b>N449:</b> A professional quality 100% acrylic exterior gloss finish recommended for wood, hardboard, vinyl, aluminum, and fiber cement sidings; unglazed brick, concrete, stucco, cinder block, and primed metal.	<ul style="list-style-type: none"> <li>• 100% acrylic latex formula - Delivers superior hide and coverage</li> <li>• Low VOC - Meets the strictest environmental standards in the industry</li> <li>• Can be applied down to 40° F - Extends the painting season</li> </ul>	Do not apply when air and surface temperatures are below 40° F (4.4° C). Do not paint vinyl siding or trim darker than the original color in general.